

Cleaning System

JET FOAMER

MOBILE FOAM GENERATOR



Jet Foamer 60 Lt



Jet Foamer 95 Lt

Jet Foamer is a powerful foam generator designed to offer easy mobility. It provides a dense and dry foam, that might be adjusted with an air injection regulator. Its rugged diaphragm with a Viton seal and its non-pressurized tank offers resistance, durability and safety for the client and user.

The 2 available models, equipped with a 9-meter hose and one 60- or 95-liters tank respectively, guarantee a complete process of sanitization with high mobility and safety.

ADVANTAGES

- Powered with compressed air.
- Designed to be easily moved.
- 60 or 95 liters tank for proportioned product, allowing easy storing and extensive application areas.
- Easy adjustment of density and distance for the foam application.
- Diaphragm pump with a Viton seal that offers a greater chemical resistance, reducing maintenance costs.
- Tank is non-pressurized, eliminating the risk of pressure accidents.
- No need of having annual certification

FEATURES

- Application hose 9 meters long.
- Foam range from 3 up to 8 meters long.
- Compressed air pressure:
Min. 2.7 bar (2.8 kgf/cm² or 40 psi)
Max. 5.5 bar (5.6 kgf/cm² or 80 psi)

APPLICATIONS



FOOD AND BEVERAGE
INDUSTRY



REFRIGERATED CELLS



KITCHEN



VEHICLE



INDUSTRIES

ISO 9001
ISO 14001
SA 8000

BUREAU VERITAS



Technical features

1. Hosebarb - 1/2" NPT x Ø 3/4"
2. Ball Valve
3. Hexhead Reducer
4. Application Wand
5. Air Valve Regulator
6. Diaphragm Pump
7. Air Filter Regulator
8. T Connection - Mixer
9. Check Valve
10. Hosebarb - 1/4" NPT x Ø 3/8"
11. Hosebarb Elbow - 1/4" NPT x Ø 3/8"
12. Hosebarb Elbow - 1/8" NPT x Ø 1/4"
13. Air Quick Connection - PU Tube 8mm
14. Extended Adapter 1/4" NPT
15. Extended Hosebarb - 1/2" NPT x Ø 3/4"
16. Hosebarb Elbow - 1/2" NPT x Ø 3/8"
17. Junction
18. Collector Filter
19. Inox Plate
20. Wheel

Cover - Internal View

